



speedtec®

17-pin
insulation insert Code 0°
housing code 1
EMC - Shielding

Technical Data

number of pins 17
temperature range -20 °C to 130 °C
clamping range Ø 6,0 mm to Ø 10,0 mm
protection type when connected IP 66/67

Electrical Data

* rated current
rated voltage
rated insulation voltage (L-L)

signal

max. 7 A
125 V (AC/DC)
2000 V

mating cycles 500

Data According to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree 3
over voltage category III
max. height for operation 2000 m

Material

housing zinc diecast / nickel plated
insulation insert PBT, UL 94 / V0
seals FKM
clamp ring brass / nickel plated

Contacts (not part of product contents)

Tools (not part of product contents)

A ST A 014 NN 00 62 0100 000



Contact Arrangement
mating view




Copyright by INTERCONTEC Produkt GmbH, Germany
All rights, including rights created by patent grant or registration
of a utility model or design, are reserved.
Noncompliance will result in seeking damages.

This document is for information only and before utilization
the user must reconfirm actuality.
Subject to technical changes.

INTERCONTEC Produkt GmbH
Bernrieder Str.: 15
D-94559 Niederwinkling
Tel.: +49 9962 2002-0
Fax: +49 9962 2002-70
E-Mail: info@intercontec.biz
Web: http://www.intercontec.biz

issue: 12.05.2017



Main Dimensions
Plug

*for max. wire cross-section
pay attention to the
cross-section of used contacts