



# Dynabrade Downdraft Sanding Table

Keep Workplace Area Free of Contaminants While Sanding

## Heavy Duty Model

### MODEL 64657

48" wide x 96" long working area.

- Includes six 20" x 25" paper filters (64658) and four 16" x 25" paper filters (64659).

#### Features

- Dual filtration – five micron pre-filter and one micron paper filters.
- High quality reverse incline blowers. Heavy-duty TEFC electric motors.
- Non-slip surface for easier tool maneuverability. Optional casters available.
- Up to 70% more filter area than competitive brands.
- Ideal for use with Dynabrade random orbital sanders.
- Base unit is all-metal construction with CNC milled 3/4" MDF table-top.
- Great for cabinet shops, solid surface fabricators and fiberglass applications.
- Keep machine on even when not in use – table actually filters air to help clean the shop environment.

#### Specifications

- **Power Source:** Two Heavy Duty TEFC Electric Motors, 1.5 Hp
- **Vacuum Suction:** Approximately 6,000 CFM
- **Sound Level:** 72 dB(a)
- **Shipping Weight:** 820 lbs.
- **Electrical Capacity:** 115 volt (single phase). 208 volt (3 phase), 230 volt (single phase), 230 volt (3 phase), 460 volt (3 phase) available upon request.
- **Two Paper Filter Sizes Available:** 64658: 20" wide x 25" long Standard Paper Air Filter  
64659: 16" wide x 25" long Standard Paper Air Filter



Model  
64657

## Standard Duty Models

### MODEL 64699

33" wide x 60" long working area.

### MODEL 64700

36" wide x 72" long working area.

#### Features

- Dual filtration – includes three 20" wide x 25" long x 2" thick pleated filters, and one pre-filter blanket.
- Includes 5" diameter casters.
- Rubberized surface on the table top is anti-static and anti-slip.
- Both tables include steel utility tray and random orbital sander hanger.

#### Specifications

- **Power Source:** One Heavy Duty Electric Motor, 1.0 Hp
- **Vacuum Suction:** 3,000 SCFM
- **Sound Level:** 72 dB(a)
- **Height:** 36" (including casters)
- **Shipping Weight:** Model 64699: 285 lbs.  
Model 64700: 365 lbs.
- **Electrical Capacity:** 110 volt, 220 volt (single phase). Three phase available upon request.
- **Two Paper Filter Sizes Available:** 64671: 20" wide x 25" long x 2" thick Standard Paper Air Filter  
64672: 20" wide x 25" long x 2" thick UL Rated Class I Non-Flammable Air Filter



Model  
64700

For Other Dynabrade Tools and Related Accessories, Visit [www.dynabrade.com](http://www.dynabrade.com)

#### DYNABRADE, INC.

8989 Sheridan Drive • Clarence, New York 14031-1490 • Phone: (716) 631-0100 • Fax: 716-631-2073  
US Consumers Call Toll Free: 1-800-828-7333

#### DYNABRADE INTERNATIONAL

8989 Sheridan Drive • Clarence, New York 14031-1490 • Phone: (716) 631-0100 • Fax: 716-631-2524  
Canadian Consumers Call Toll Free: 1-800-344-1488

#### DYNABRADE EUROPE S.à.r.l.

Zone Artisanale • L-5485 Wormeldange—Haut, Luxembourg • Phone: 352 76 84 94 1 • Fax: 352 76 84 95 1

#### DISTRIBUTED BY:



Try Our New U.S. Consumer Toll Free Number: 1-888 DYNABRADE