


# TECHNICAL DATA SHEET

TDS 958 / Index 01 - 15/09/2014

958



# LEAK DETECTOR

# **GAS LEAK DETECTOR**



## **DEFINITION**

Gas leak detector approved for use in nuclear power plants (PMUC authorisation from the EDF).

## **ADVANTAGES**

Ecological.
Biodegradable.
Effective even for small leaks.
Non-toxic.
Non-corrosive.

Complies with standard NF EN 14291

# **APPLICATION FIELDS**

Piping, taps, connections, water works, pipes, valves.

Natural gas vehicles feed system.

Compressed air installations, gas-cylinder pressure gauges, refrigeration installations.

LEAK DETECTOR 958 contains no mineral oils and is suitable for use with all gases, including oxygen.

## **TECHNICAL CHARACTERISTICS**

Aspect	liquid
Colour	
Flash point	none
Boiling point	>100°C
pH	8.5
CI, F, S	< 200 ppm

#### 1/2 Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com

ORAPI ® cannot know about every application for which the products are used nor their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.



# TECHNICAL DATA SHEET

TDS 958 / Index 01 - 15/09/2014

# **INSTRUCTIONS FOR USE**

Spray on the area to be examined. Bubbles will form at the site of the leak.

# **STORAGE**

Do not store pressurised container at temperatures below 50°C; do not freeze. Keep pressurised container away from all sources of ignition.

# **SAFETY**

The active product poses no particular danger, but is an irritant if it comes into contact with eyes.

# **PACKAGING**

Aerosol 650 ml

ref. 6958A4

x 12

# **CERTIFICATION**



Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com